



25 YEARS COLOR LOCKED





PERFORMANCE LEVEL

U-VALUE		1.6 W/m²K*
UF-VALUE KADER/VLEUGEL		2.9 W/m²K
AIR TRANSMISSION	NBN EN 12207	Klasse 4
WATERTIGHTNESS	NBN EN 12208	Klasse E9A
RESISTANCE TO WIND	NBN EN 12210	Klasse C4
SHOCK RESISTANCE	EN 13049	Klasse 5
BURGLARPROOF	NEN 5096 & ENV 1627	RC2
OPERATING FORCE	EN 13115	Klasse 1
ACOUSTICAL INSULATION		tot 45.2dB (-1; -3)

^{* 1230}mm x 1480mm / UG 1.0W/m²K & PSI 0.036W/MK / profile combination: FT010-FT020

UITVOERING

- Fixed frames for double glazing
- Single or double sash side-hung open in windows.
 Tilt in only windows
- Flat door, inward en outward opening
- · Rebate door, inward en outward opening
- Possibility to bend the profiles like round frames, pointed and basket handle archs

TECHNICAL FEATURES

• Built-in depth window: frame: 65 mm - sash: 74 mm

• Glazing rebate: 22 mm

• Glazing: frame: 12-72 mm - sash: 21-81 mm

100% MADE IN BELGIUM



Aliplast develops aluminium profiles tailored to current housing needs. Everything happens under one roof: from drawing to extrusion, powder

coating, insulation and transport to the Aliplast distributors. The distributors produce and install the finished windows in your building project.

25-YEAR COLOUR GUARANTEE



Aliplast gives a 25-year guarantee on 50 current colours. The Qualicoat Seaside quality label ensures that your paint colour is extra protected against

aggressive environments (exhaust fumes, salty sea air, etc.). You enjoy a 15-year guarantee on all other colours. Peace of mind for the future.

DURABLE PRODUCT



Aluminium is a durable product because it has a long lifespan. Moreover, the material is fully recyclable and can therefore be completely reused without

compromising on quality. Aliplast mainly uses recycled aluminium billets for architectural systems. This aluminium is "Green Metal". It has a positive impact on people and the environment.